

# Decor Panels- Roundprofile

Product data sheet and technical information



Issued: August 2013

## Pure Style; Bright Style; Ambient Style

Classification	Decor Panels	
Deckmaß	1242/1992/2492/2992/3492/3992/ x 178/188 x 12 mm;	
Profile	Invisible joint	
Base board	MDF (740+/-30 kg/m <sup>3</sup> ) E-1	
Packing unit	1250 mm:6 pieces per carton (ca. 1,47 m <sup>2</sup> ) 2000 mm:6 pieces per carton(ca.2,35 m <sup>2</sup> ) 2500 mm:6 pieces per carton (ca. 2,94 m <sup>2</sup> ) 3000 mm:6 pieces per caron (ca.3,53 m <sup>2</sup> ) 3500 mm:6 pieces per carton (ca. 4,12 m <sup>2</sup> ) 4000 mm:6 pieces per carton (ca.4,70 m <sup>2</sup> )	
Surface structure	matt; matt-gloss	
Surface material	High quality, environmentally friendly paper or lacquer based surface.	
Suitable for use in kitchen and bathrooms	Yes, with adequate ventilation and no direct contact with water.	
Garantie	2 years	
Moisture content according to DIN EN 322	6 % +/-2	
Sand content according to ISO 3340	< / =0,05 %	
Heat resistance and colour fastness according to DIN V	Suitable for the installation of ter Hürne LED and halogen lamps bearing the MM test	
Flammability according to DIN EN 13501-1	Dfl	
Light fastness according to DIN EN 13329	Blue wool scale ≥ 6	
Packaging	Pure and recyclable	



## General requirements according to Product standard DIN 68740-2

Thickness of the element	+ / - 0,5 mm
Length of the surface layer	+ / - 2 mm
Width of the surface layer	+ / - 1 mm
Squarness of the element	on 1 m side length 2 mm= 0,2%; max. 0,3 mm
Straightness of the surface layer	1 mm per meter = 0,1 %
Openings between elements	< / = 0,30 mm
Height differences between elements	< / = 0,40 mm