

Decor Panels - Soft profile

Product data sheet and technical information



Issued: August 2013

Pure Style; Bright Style; Ambient Style

Classification	Decor Panels	
Dimensions (cover surface)	1235/2485 x 220 x 12 mm;	
Profile	Invisible joint	
Base board	MDF (740+/-30 kg/m ³) E-1	
Packing unit	1250 mm:6 pieces per carton (ca. 1,763 m ²) 40 cartons per pallet (ca. 70,50 m ²) 2500 mm:6 pieces per carton (ca. 3,525m ²) 24 carton per pallet (ca. 84,60 m ²)	
Surface structure	matt; matt-gloss	
Surface material	High quality, environmentally friendly paper or lacquer based surface.	
Suitable for use in kitchen and bathrooms	Yes, with adequate ventilation and no direct contact with water.	
Garantie	2 years	
Moisture content according to DIN EN 322	6 % +/-2	
Sand content according to ISO 3340	< / =0,05 %	
Heat resistance and colour fastness according to DIN VDE 0109 Teil 559	Suitable for the installation of ter Hürne LED and halogen lamps bearing the MM test	
Flammability according to DIN EN 13501-1	Dfl	
Lichtechtheit nach DIN EN 13329	Blue wool scale ≥ 6	
Verpackung	Pure and recyclable	

General requirements according to Product standard DIN 68740-2

Thickness of the Element	+ / - 0,5 mm
Length of the surface layer	+ / - 2 mm
Width of the surface layer	+ / - 1 mm
Squarness of the element	on 1 m side length 2 mm= 0,2%; max. 0,3 mm
Straightness of the surface layer	1 mm per meter = 0,1 %
Openings between the elements	< / = 0,30 mm
Height differences between elements	< / = 0,40 mm