

floors@work/55

floors@work/80

Covering type according to EN ISO 10582	Heterogeneous Planks / Tiles, type 1	
Number of colours	78 planks / 31 tiles	10 planks
Packaging per box/pallet	3.34 m <sup>2</sup> /200.40 m <sup>2</sup> 600x600 mm: 3.24 m <sup>2</sup> /194.40 m <sup>2</sup>	
Performance classification EN ISO 10582 / ISO 10874	23, 33, 42	23, 34, 43
Total thickness ISO 24346	2.5 mm	
Wearlayer thickness ISO 24340	0.55 mm	0.8 mm
Surface treatment	yes/PU	
Bevelled edges	yes (depending on design)	
Total weight ISO 23997	3.81 kg/m <sup>2</sup>	3.72 kg/m <sup>2</sup>
Residual indentation ISO 24343-1	≤ 0.1 mm*	
Dimensional stability ISO 23999	≤ 0.15 %*	
Castor chair suitability ISO 4918	yes – using EN 12529, Typ W	
Underfloor heating EN 1264-2	suitable up to 28°C	
Behaviour to fire EN 13501-1	Bfl-s1	
Resistance to thermal conductivity ISO 8302 / EN 12667	0.02 m <sup>2</sup> K/W	
Electrical propensity when walked upon EN 1815	< 2 kV	
Impact sound improvement ISO 10140-3	4 dB	
Colour fastness to artificial light ISO 105-B02/2	≥ 7	
Electrostatic characteristics EN 1081	> 10 <sup>12</sup>	
Chemical resistance ISO 26987	conforms**	
Slip resistance	R9 to R10 (depending on design resp. emboss: details available on request)	
Adhesive recommendation	see installation instruction	
Maintenance/Cleaning recommendation	Dr. Schutz	

\* Averaged value

(Date: 01/01/2019)

\*\* Vis-à-vis the short-term effects of normal, domestic agents.

Please also note the installation and cleaning and care instructions.

